

# StatMatic

## VOLUMERANGES

50µL - 250µL	250µL - 500µL	0.5-2.5mL
--------------	---------------	-----------

## PERFORMANCE

Precision (CV) @ full volume	50-250µL < 1%		250-500µL < 1%		0.5-2.5mL < 1%	
Accuracy	µL	±%	µL	±%	mL	±%
	250	1	500	1	2.5	1
	200	1.5	400	1.25	1	2
	100	2	300	1.6	.8	2.5
	50	4	250	2	.5	3

## PHYSICAL

Dimensions (instrument only)  
 6 in. Or 15.2cm. Length  
 .795in. Or 2.02cm. handle diameter  
 Weight 1.3oz. Or 39.69gm. (instrument only)  
 6.3oz. Or 179gm. (shipping weight)

Appearance Tan Body & Knob-OR-Gray Body & Teal Knob  
 Black Hot Stamping

## FLUID CONTACT MATERIALS

Polypropylene  
 Glass  
 Teflon Plungers

## UNIT COMES COMPLETE WITH

20mm, 24mm & 28mm Threaded Adapters  
 7in Inlet Tubing  
 4.5in Outlet Delivery Tube  
 25in Remote Delivery Tube  
 Volume Calibration Rings  
 Instructions

## ACCESSORIES

125cc HDPE Bottle w/ 3.65in. Tubing inlet & adapter  
 8-port Manifolds- non sterile/disposable  
 Fixed Outlet Tubing  
 Repair Kit